

MILITEC LTD

C9800M TABLET CONTROLLER



The C9800M Tablet Range Controller is a user-friendly handset designed for both left and right-handed operators, on indoor and outdoor ranges.

When used in conjunction with the C9004RM Interface unit it enables the operator to control targets from 0mtrs to 1000mtrs (10s).

The Home screen's drop-down menu allows manual control of ALL or Selected Individual targets or Groups via the A (FACE A), I (EDGE), B (FACE B) buttons which are displayed on both sides of the screen.

The C9800M features: -

- i) Targets can be set into Groups if required
- ii) Target exposure and away times may be set between 1 and any number up to 99 seconds
- iii) Repeat sequences from 1-99
- iv) Shoot programs can be saved
- v) Each shoot's verbal instructions may be saved and displayed prior to the start of the selected program
- vi) When hit sensing is available, features such as Bounce Back and Turn When Hit after a selected number of hits, and recording of the time between target exposure to the first bullet hit, are included
- vii) The C9800M software may be used with a moving target carrier which can be controlled separately or included with other targets on the range

C9800M SPECIFICATIONS

Weight	800g
Size	228mm x 145mm x 16.5mm (H x W x D)
Power	3.7V 9000mAh battery (with up to 8 hours battery life)
Display	8 inch, high-brightness screen (resolution up to 1280x800) Blue light filtering and anti-dazzle for improved outdoor use High strength tempered Touchpad which is glove touch and water spray capable
OS	Windows 10 professional (64bit)
Environmental	The tablet meets MIL-STD 810G and IP65 standards
Drop Height	1.2m composite wood floor, in operation status
Operating Temperature	-10 to 60 °C
Storage Temperature	-30 to 70 °C
Humidity	95% Non-Condensing

C9004RM-WIFI INTERFACE SPECIFICATIONS

The Radio Interface Unit provides the communications link between the C9800M and the radio controlled target mechanisms.

The C9004RM-WiFi is available in two options;

- a) For portable use
- b) For fixed installations

Weight	Portable option	2.5 kilos
	Fixed installation	2 kilos
	USB option	2 kilos
Size	60mm x 190mm x 240mm (H x W x D)	
Comms	WiFi and 400-460MHz 100mW	