

## MILITEC LTD

## M2200MF FAST TURNING TARGET MECHANISM



The M2200MF is a dedicated fast turning target mechanism designed for basic classification and judgement/decision shooting

The power unit for the M2200MF can be portable or fixed, battery powered and radio controlled or mains powered with line or radio control.

The power unit itself is fitted within a tubular frame, which provides a stable platform.

In the portable mode a separate 12Vdc power pack is connected to the unit by means of a 'Quick Fit 'military bayonet type connector.

In the Fixed mode the 12Vdc is supplied from a separate power supply unit 220/240Vac to 12Vdc.

## **SPECIFICATIONS**

WEIGHT 17 Kilos (without battery pack)

SIZE (WITHOUT BATT. PK) 400mm x 300mm x 330mm (LxWxH)

TURN TIME 0.3 sec. (edge to face)

HIT SENSING Internally mounted and remotely adjusted

EXPOSURE SETTINGS 1 to 99 seconds in steps 1 second

**OPERATIONAL** 

TEMPERATURE -15C to 65C

OPERATIONAL DISTANCE Up to 1000m

RADIO FREQUENCY 400Mhz to 460Mhz

TARGET SILHOUETTE Max Size 1220x460mm Aluminium /8mm Plywood /

Rigid Plastic Max Weight 3kg

CONTROL Integral Radio Transceiver

IP PROTECTION IP65

CONSTRUCTION Corrosion resistant treated steel FINISH Typical dark green, BS381C



## GENERAL FEATURES

RADIO Control 1-256 individual targets with eight separate radio channels

available.

Operational range up to 1000 Metres line of sight.

HIT SENSING Internally mounted hit sensor set remotely from the handset.

Target response to hits set from the handset

Minimum sensitivity 100 Joules

OPERATION CAPABILITY Vertical turning only. 0.30sec. from Edge to Face

A fully charged battery has sufficient capacity to turn a standard Fig.11

target in excess in excess of 2500 times.

POWER AC375 Mains power pack 110Vac/240Vac to 12Vdc

ACO05 Portable battery pack 12Vdc with status indication and "Quick Fit"

military bayonet type connector. Weight 4.5 kilos.

FRAME The tubular steel frame provides extra protection, aids carrying

and provides a stable location when in use.

CONSTRUCTION The enclosures are manufactured from zinc coated sheet steel and

finished in polyester powdered paint that is stoved to provide a hard and

durable finish.

All metal fixings used are manufactured from stainless steel.

CONTROL C9090M, C9172M, C9200M & C9800M Handsets