

# MILITEC LTD

## BATTERY CHARGERS

Single and Multiple output battery chargers for use with the AC005 Portable Battery pack.

### Mode of Operation

The chargers provide a completely automatic charging system where an initial boost charge, as indicated by the red boost LED, is provided until at least 90% of the battery's capacity has been restored, then the output is automatically switched to trickle charging with the green LED flickering before becoming steady indicating a fully charged battery. The battery may be left connected indefinitely without causing any damage.

### MULTIPLE OUTPUT B225-4 SPECIFICATIONS



#### Weight

12 kilos

Four outputs

Each 13.8Vdc

Input 240Vac 3A

#### Dimensions

500mm x 300mm x

240mm (L x W x H)

### SINGLE OUTPUT B215v2 SPECIFICATIONS



#### Weight

2 kilos

Single output

240Vac 3A input.

#### Dimensions

200mm x 165 x

105mm (L x W x H)

For multiple charging of AC005 battery packs simultaneously the B225-4 can be supplied fitted to racks.



### AC005 SPECIFICATIONS



#### Weight

4.5 kilos

12Vdc. 13 Ahr sealed lead acid battery

Tri coloured LED provides battery status indication.

#### Dimensions

175mm x 120mm x 130mm (L x W x H)