

# MILITEC LTD

## M3200M POP-UP WITH LOMAH



A lightweight steel frame, the AC120 accommodates both, the M3200M Pop-Up and LOMAH H-Bar for portable applications.

For fixed applications, such as the units requiring to be installed in a pit, then special frames to suit the range can be made.

Quick fit locking clamps enables the arrangement to be set up in a couple of minutes.

The AC005v3 detachable battery pack provides the 12Vdc for both units.

On occasions where only the Pop-Up is required, the LOMAH H-Bar need not be fitted.

### SPECIFICATIONS

#### AC120 LOCATION FRAME

##### DIMENSIONS

1055 mm x 450 mm x 215 mm LxWxH

##### WEIGHT

12kg approx

##### CONSTRUCTION

The enclosures are manufactured from zinc coated sheet steel and finished in polyester powdered paint that is stoved to provide a hard and durable finish.

All metal fixings used are manufactured from stainless steel.



## LOMAH H-BAR

ACCURACY	+/- 5 mm in center scoring area
MIN. VELOCITY	1,150 fps (350 m/s) at target
RADIO RANGE	Line of sight out to over 2000m
POWER	Rechargeable batteries available with over 6+ hours of run time
WEIGHT	10kg approx
DIMENSIONS	1200 mm x 450 mm LxW

## M3200M POP-UP MECHANISM

WEIGHT	25 Kilos (without battery pack)
SIZE (WITHOUT BATT. PK)	470mm x 400mm x 380mm LxWxH
RADIO	Control 1-256 individual targets with eight separate radio channels available. Operational range up to 1000 Metres line of sight.
HIT SENSING	Externally mounted hit sensor set remotely from the handset. Target response to hits set from the handset Minimum sensitivity 100 Joules
OPERATION CAPABILITY	A fully charged battery has sufficient capacity to lift and lower a standard Fig.11 target in excess of 2000 times.
POWER	AC375 Mains power pack 110Vac/240Vac to 12Vdc AC005 Portable battery pack 12Vdc with status indication and "Quick Fit" military bayonet type connector. Weight 4.5 kilos.
FRAME	The tubular steel frame provides extra protection, aids carrying and provides a stable location when in use.
CONSTRUCTION	The enclosures are manufactured from zinc coated sheet steel and finished in polyester powdered paint that is stoved to provide a hard and durable finish. All metal fixings used are manufactured from stainless steel.